

ANSI High Temperature Glassfibre Twin Twisted Exposed Welded Tip Thermocouples with Miniature or Standard Plug Termination





Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.



Datasheet

Need Your Temperature Sensor calibrated?

Traceable to ISO17025 (UKAS) calibration standards, Labfacility offer a choice of a 3 or 5 point traceable calibration using our in-house calibration facility.

Please be aware that if you add a calibration option to your order you will be contacted regarding delivery information.

Specifications

Specifications

General Description	Fast response, welded exposed junction. Good temperature resistance (not suitable in fluids).
Thermocouple Type	К
Thermocouple Junction	Exposed
Cable Length	STD Plug: 5M, 10M, 20M / MINI Plug: 5M, 10M, 25M
Cable Type	high temperature glassfibre insulated twisted cable
Core / Strands	1/0.711mm conductors (21awg)
Cable Termination	Miniature or Standard plug termination
Max. Temperature	+700°C
Min. Temperature	0°C
Tolerance	Tolerance to ANSI MC96.1 Class 2
Standards Met	Colour code to ANSI MC96.1