

4-20mA remote wall mounted housing, Pt100 input with PFA cable & PRT sensor - 1M cable length



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Housing moulded in general purpose ABS, the external fixing points provide a simple and rapid means of mounting sensors directly onto ducts, dispensing with the need for separate mounting plates.

Need Your Temperature Sensor calibrated?

Traceable to ISO17025 (UKAS) calibration standards, Labfacility offer a choice of a 3 or 5 point traceable calibration using our in-house calibration facility, you can select any temperature points between -10°C & +200°C.

Please be aware that if you add a calibration option to your order you will be contacted regarding delivery information.

Specifications

Specifications

Product Code	XE-5660-001
General Description	Compatible with Pt100 platinum resistance thermometers
Sensor Type	Surface Mounting for remote installation
Probe Diameter	6mm
Probe Length	250mm
Cable Length	1m
Cable Type	PFA screened
Core / Strands	7/0.2mm
Head Type	High Impact ABS Plastic Construction
Thread	Entry Threads M16
Transmitter	Yes
Range	-50°C to +150°C
Output	4-20 mA output