



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

0.5mm Diameter Fast Response Thermocouple with threaded pot & tails IEC Type K - Insulated Junction - 100mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Type K with threaded pot & tails in 310 stainless steel

For 0.25mm, 0.75mm & 0.81mm diameter and for Inconel® Alloy 600 sheath versions, please use our [custom sensor forms](#) to submit your requirements or email sales@labfacility.com / telephone our sales line 01243 8712

Need Your Temperature Sensor calibrated?

Traceable to ISO17025 (UKAS) calibration standards, Labfacility offer a choice of a 3 or 5 point traceable calibration using our in-house calibration facility, you can select any temperature points between -10°C & +200°C.

Please be aware that if you add a calibration option to your order you will be contacted regarding delivery information.

Specifications

Specifications

| | |
|-----------------------------|---|
| Product Code | XE-0163-001 |
| General Description | Type K with threaded pot & tails in 310 stainless steel |
| Sensor Type | Mineral Insulated |
| Thermocouple Type | K |
| Element/hot junction | Single element, junction insulated |
| Probe Diameter | 0.5mm |
| Probe Length | 100mm |
| Sheath Material | 310 stainless steel |
| Pot Type | M8 x 1.0mm fine pitch threaded pot seal (200°C) |
| Cable Length | 100mm |
| Cable Type | PFA insulated twin twisted IEC |
| Core / Strands | 7/0.2mm |
| Termination Type | Bare Tails |



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

| | |
|-------------------------|----------------------------|
| Max. Temperature | +650°C |
| Min. Temperature | -40°C |
| Standards Met | In accordance with IEC 584 |