



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

0.81mm Diameter Fast Response IEC Thermocouple Plain pot seal with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails - Grounded Junction - 150mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

If you require larger quantities, please email sales@labfacility.com or telephone our sales line 01243 871280.

Need Your Temperature Sensor calibrated?

Traceable to ISO17025 (UKAS) calibration standards, Labfacility offer a choice of a 3 or 5 point traceable calibration using our in-house calibration facility.

Please be aware that if you add a calibration option to your order you will be contacted regarding delivery information. .

Specifications

Specifications

| | |
|-----------------------------|--|
| Product Code | XE-0225-001 |
| General Description | Plain pot seal (200°C) with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails. |
| Sensor Type | Mineral Insulated |
| Thermocouple Type | K |
| Element/hot junction | Single element, junction grounded from sheath |
| Probe Diameter | 0.81mm |
| Probe Length | 10mm |
| Sheath Material | K - Stainless steel 316 |
| Pot Type | Plain (+200°C) |
| Cable Length | 1M |
| Cable Type | PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584) (Max Temp 250°C) |
| Core / Strands | 7/0.2mm |



| | |
|------------------|----------------------------|
| Termination Type | Bare Tails |
| Max. Temperature | K +650°C |
| Min. Temperature | K -40°C |
| Tolerance | Class 1 |
| Standards Met | In accordance with IEC 584 |
| Probe Material | 304 stainless steel |