General Purpose Thermistor Probe with PFA lead - 4.5mm tube diameter, 150mm tube length



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

2-wire 10K NTC thermistor housed in a stainless-steel sheath with a temperature range of -50 to +150°C, is a versatile temperature sensing device.

The stainless-steel sheath provides durability and protection, making this thermistor ideal for a wide range of applications, from industrial processes to consumer electronics and scientific research.

Key Features:

Resistance Value: 10K ohms

Type: NTC (Negative Temperature Coefficient) thermistor, meaning its resistance decreases as the temperature increases.

Temperature Range: Capable of accurately measuring temperatures from -50°C to +150°C.

Wiring: 2-wire configuration for simple connectivity.

Design: Encased in a stainless-steel sheath for enhanced durability and protection against harsh environments

Applications:

Environmental Monitoring

HVAC Systems
: Monitors air temperature to regulate heating, ventilation, and air conditioning systems efficiently.

Climate Control Devices
: Ensures accurate temperature readings in smart thermostats and other climate control devices.

Industrial Processes

Equipment Monitoring
: Ensures the safe operation of machinery by monitoring and controlling operating temperatures.

Process Control
: Maintains precise temperatures in manufacturing processes, such as in chemical production, food processing, and material fabrication.

Specifications

Specifications

Product Code	XE-9847-001
General Description	2-wire 10K NTC thermistor housed in a stainless steel sheath
Thermistor	10K NTC Thermistor
BETA 25/85	3977K
Probe Diameter	4.5mm
Cable Length	2M
Cable Type	PTFE insulated twisted leads
Core / Strands	7/0.2mm
Cable Termination	Bare Tails
Max. Temperature	+150°C
Min. Temperature	-50°C
Accuracy	+/- 0.2K (over 0-70°C)
Length	150mm
Number of Wires	2
Series	Thermistor Probes 10k